

HIGH PERFORMANCE TIMING SET FEATURES CHART

PartNo.	Fitment	Grade	Camshaft Sprocket	Crankshaft Sprocket	Keyway	Max Advance Camshaft	Max Retard Camshaft	Timing Chain Type	Center Distance	Includes
40201	GM 3.3L - 6.6L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.200" Seamless DR	4.521"	
40202	Chrysler 5.2L - 6.4L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.200" Seamless DR	6.125"	
40203	Chrysler 5.9L - 7.2L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.220" Seamless DR	5.152"	
40204	Ford 5.8L - 7.0L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.220" Seamless DR	5.044"	
40205	GM BB	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.220" Seamless DR	5.125"	
40206	Ford 4.2L - 5.8L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.200" Seamless DR	4.804"	
40217	Chrysler 5.9L - 7.2L	Performance	Cast Iron	Cast Iron	3 Keyway	2°	2°	.220" Seamless DR	5.125"	
40400	GM SB	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	4.521"	
40401	GM SB	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	5.512"	
40402	Ford 4.3L - 5.8L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	4.804"	
40403	Ford 7.0L, 7.5L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	N/A	N/A	.250" Seamless DR	6.078"	
40404	GM 3.0L - 4.1L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	N/A	N/A	.250" Seamless DR	4.335"	
40405	Ford 5.8L & 6.6L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	N/A	N/A	.250" Seamless DR	5.044"	
40406	Chrysler 4.5L - 6.4L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	N/A	N/A	.250" Seamless DR	6.125"	
40407	Chrysler 5.9L - 7.2L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	5.152"	
40408	GM 5.3L - 7.5L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	5.192"	
40409	GM 4.3L - 7.5L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	5.044"	
40410	Ford 5.8L - 7.0L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.250" Seamless DR	5.044"	
40500	GM 4.3L - 6.6L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.335" Seamless SR	4.521"	
40510	GM 6.5L - 7.4L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	3 Keyway	2°	2°	.335" Seamless SR	5.152"	
40520	GM 5.0L & 5.7L	Performance	Induction Heat Treated Cast Iron	Heat Treated Billet Steel	9 Keyway	4°	4°	HY-VO Silent Chain	4.521"	
40540	Chrysler 5.7L & 6.1L	Performance	Stainless Steel	Heat Treated Billet Steel	6 Keyway	6°	4°	Silent Chain	N/A	Tensioner
48500T-9	GM SB	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	N/A	Thrust Bearing
48500W-9	GM 3.3L - 6.6L	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	Seamless DR	4.521"	Thrust Washer
48510T-9	GM BB	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	5.152"	Thrust Bearing
48510W-9	GM BB	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	5.125"	Thrust Washer
48520T-9	Ford 4.2L - 5.8L	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	4.804"	Thrust Bearing
48520W-9	Ford 4.2L - 5.8L	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	4.804"	Thrust Washer
48530T-9	Ford 7.0L & 7.5L	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	6.078"	Thrust Bearing
48551T-9	Ford 5.0L & 5.8L	Performance	Billet Steel	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	4.804"	Thrust Bearing
48560T-9	GM LS 4.8L - 6.0L	Performance	3 Bolt Billet Steel; 0 / 1 Sensor; 24x Reluctor	Billet Steel	9 Keyway	4°	4°	.250" Seamless SR	4.890"	Thrust Bearing
48561T-9	GM LS 4.8L - 6.0L	Performance	3 Bolt Billet Steel; 0 / 1 Sensor; 24x Reluctor	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	4.890"	Thrust Bearing
48562-6	GM LS 4.8L - 6.0L	Performance	3 Bolt; Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	6 Keyway	6°	4°	.250" Seamless SR	4.890"	
48562T-9	GM LS 4.8L - 6.2L	Performance	3 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless DR	4.890"	Thrust Bearing
48563-6	GM LS 7.0L	Performance	3 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	6 Keyway	6°	4°	.250" Seamless SR	4.890"	
48563T-9	GM LS 7.0L	Performance	3 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless DR	4.890"	Thrust Bearing
48564T-9	GM LS 4.8L - 6.2L	Performance	1 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless SR	4.890"	Thrust Bearing
48565T-9	GM LS 4.8L - 6.2L	Performance	1 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless DR	4.890"	Thrust Bearing
48566T-9	GM 5.0L, 5.7L	Performance	Billet Steel	Heat Treated Billet Steel	9 Keyway	8°	8°	.250" Seamless DR	4.521"	Thrust Bearing
48567T-9	Chrysler 5.7L & 6.1L	Performance	Stainless Steel	Heat Treated Billet Steel	9 Keyway	N/A	N/A	.250" Seamless DR	4.521"	Thrust Bearing
48568-3	GM 5.0L & 5.7L	Performance	Cast Iron	Stainless Steel	9 Keyway	N/A	N/A	.335" Seamless SR	4.521"	
48569-9	GM 5.0L & 5.7L	Performance	Cast Iron	Stainless Steel	9 Keyway	N/A	N/A	.335" Seamless SR	4.521"	
48570T-9	GM LS 4.8L - 6.2L	Performance	3 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless SR	4.890"	Thrust Bearing
48571T-9	GM LS 7.0L	Performance	3 Bolt Stainless Steel; 4 Sensor; 58x Reluctor	Billet Steel	9 Keyway	8°	8°	.250" Seamless SR	4.890"	Thrust Bearing
48572T	GM SB W/O Roller Camshaft	Performance	2 Piece Adjustable Billet Steel	Heat Treated Billet Steel	Single Keyway	6°	6°	.250" Seamless DR	4.521"	Thrust Bearing
48573T	GM BB W/O Roller Camshaft	Performance	2 Piece Adjustable Billet Steel	Heat Treated Billet Steel	Single Keyway	6°	6°	.250" Seamless DR	5.125"	Thrust Bearing
48574T	GM SB	Performance	Cast Iron	Billet Steel	9 Keyway	4°	4°	.250" Seamless DR	4.521"	Thrust Bearing